

FICHA TECNICA: DATUM



Tile Name	Datum Modular
Product Type	Modular
Construction	Tufted
Surface Texture	Level Patterned Loop
Gauge	1/12 (49.00 rows per 10 cm)
Density	6120
Weight Density	104,040
Sustainable Content	Contains a minimum 35% pre-consumer recycled content by total weight
Stitches Per Inch	9.3 (36.61 per 10 cm)
Finished Pile Thickness	.100" (2.54 mm)
Dye Method	Solution Dyed
Backing Material	EcoFlex ICT
Fiber Type	Colorstrand® SD Nylon
Face Weight	17.0 oz. per sq. yd. (576 g/m2)
Pattern Repeat	Not Applicable
Size/Width	24" x 24" (.6096 m x .6096 m)
Soil Release Technology	Sentry Plus
Installation Method	Monolithic, Quarter Turn, Vertical Ashlar, Brick Ashlar, Multi-Directional
Indoor Air Quality	Green Label Plus 1098
Foot Traffic	Heavy
Recommendation TARR NSF 140	Gold (Platinum option available)

PERFORMANCE

Static	AATCC-134 Under 3.5 KV
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450

WARRANTIES

Warranties	Lifetime Limited Modular Warranty
	Lifetime Limited Colorfastness to Light
	10 Year Limited Colorfastness to Atmospheric Contaminants
	10 Year Stain Warranty
	Lifetime Static